



Dolphin Interconnect Solutions

eXpressWare

Software release notes

for PX products

5.19.2

Date: 17th February 2022

Table of Contents

Definitions.....	3
Release categories.....	3
Release version scheme.....	4
Types of releases.....	4
Release candidate.....	4
Release.....	4
Dolphin eXpressWare.....	5
SuperSockets.....	5
SuperSockets User-space Library for Windows and Linux.....	5
SuperSockets Kernel Space library for Linux.....	5
Dolphin technical support and documentation.....	6
Supported Hardware and configurations.....	7
Supported Dolphin products.....	7
Configurations supported by this release.....	7
Standard firmware revisions.....	8
Support for OEM hardware.....	8
General eXpressWare defaults and settings for PX.....	8
Dolphin eXpressWare PX release 5.19.2 Linux.....	10
Dolphin eXpressWare PX release 5.19.2 Windows.....	16
Dolphin eXpressWare PX release 5.19.2 RTX.....	19
Dolphin eXpressWare PX release 5.19.2 VxWorks.....	21

Definitions

Release categories

The following definitions are used for the eXpressWare software.

Prototype:

Only parts of the full functionality is implemented. No or little error handling. The purpose of a prototype release is to demonstrate some limited important functionality to a selected number of customers. Should normally not be made generally available.

Alpha:

All functionality implemented. Limited error handling. Can be released to collaborating partners.

Beta:

Error handling and performance optimization completed. Very close to the final product. Can be made available on a general basis.

GA:

General Availability. Well tested product that can be shipped to OEM customers and end users.

Snapshot:

A snapshot release (or code drop) can be done at any of the above defined release categories. Code distributed by an individual, as a part of an agreed collaboration etc for the purpose of testing a fix or new functionality requested by the other party. Snapshot releases are generally not supported by Dolphin, but used as an important part of the test and qualification of new code. The person doing the snapshot is responsible for making sure the letter «d» (for development) is added to the version string before distributing the software and to make sure the other party understands the terms (not supported) and conditions of the software release. The person doing the snapshot release should make sure to keep an exact copy of the release (by a private copy or source control tag), no other formal steps are required.

Release version scheme

All eXpressWare components have a version string that easily can be retrieved by users to identify the product and the release version. The version string is constructed using decimal numbers formatted like MAJOR_VER.MINOR_VER.BUGFIX_VER (E.g. DIS 5.7.0).

MAJOR_VER

Major changes to the software. Significant improvements or changes that may require changes to how the product is used.

MINOR_VER

Changes to the software that significant improve functionality. Minor changes and improvements that does not affect general usage of the product. Fixes to support new versions of operating systems. Bug fixes.

BUGFIX_VER

Minor Bug fixes to a previously released software. No functionality or general improvements are allowed.

The letter “d” should always be added to the version string while the code is being implemented to specify that the running code is an internal development version. Snapshot releases should always display the letter “d”.

Types of releases

Two types of releases are used by Dolphin to satisfy rapid development, concurrent external testing and stability and long term test requirements. The ideas are collected from and widely used within the Linux community. These two types applies to Prototype, Alpha, Beta and GA releases.

Release candidate

A release candidate is a release that is still undergoing testing and qualification. The purpose of distributing release candidates is to enable customers and partners to have access to updated drivers without having to wait for the final release. The only difference between a release candidate and a release is the amount of testing performed. The release note should specify if this is a release candidate or a completely tested release. Critical bugs found during release candidate testing may cause the release to be canceled. In such cases, the version date/string of the release must be changed before a new release candidate can be produced following the general release engineering steps.

Release

A release is a product that have completed the full release procedure.

Normally a release candidate will be renamed to a release if all tests are passing and no new critical bugs are found. This will be reflected in the release note.

Dolphin eXpressWare

The eXpressWare software suite includes the following components. Please note that all combinations of components, PCIe cards and operating systems may not be supported. Please refer to the release note for each operating system and card for details.

IRM	Interconnect Resource Manager
SISCI	Software Infrastructure for Shared-Memory Cluster Interconnects. This includes binaries , sources, documentation and development tools.
SuperSockets	Socket accelerator for PCIe
IPoPCIe	TCP-IP driver for PCIe. Windows NDIS driver or Linux DISip.
SmartIO	Sharing and access to IO management and control. Includes Device Lending and SISCI SmartIO management.
IO Monitoring	Transparent Board Management Software for transparent PCIe adapter cards and cable connections.

SuperSockets

Dolphins SuperSockets is a family of Berkeley Sockets API compliant libraries that will accelerate embedded applications written to standard networking functionality. The functionality depends on the implementation approach.

SuperSockets User-space Library for Windows and Linux

The Dolphin SuperSockets user space library is currently provided for the purpose of supporting embedded applications. The Windows Winsock2 environment contains a rich set of socket functions and options. SuperSockets version 5.2 and newer adds support for connectivity to the new Linux SuperSockets user space library. We have verified and supports the following socket calls:

accept, bind, connect, getpeername, getsockname, getsockopt, listen, recv, select, send, setsockopt(TCP_NODELAY), shutdown, socket.

For Windows OS, specific functions are implemented: closesocket,WSASendDisconnect, ioctlsocket, WSAAsyncSelect, WSAGetOverlappedResult, WSAIoctl, WSAREcv, WSASend and WSASendDisconnect.

For Linux OS, normal file operations are implemented: close, ioctl.

SuperSockets Kernel Space library for Linux

The SuperSockets Kernel-space library is our standard recommendation for most standard applications. It implements a new socket address family AF_SSOCKS, and support virtually all networked Linux applications. The software is also compliant with the Linux Kernel Sockets API and can also be used by kernel services that can be configured to use AF_SSOCKS (decimal value 27). This version of SuperSockets includes automatic fail-over to Ethernet if there is a failure with the PCIe network.

UDP multicast is supported if the underlying PCIe hardware and topology supports multicast. Currently, only a single receiver per node for a specific multicast groups is supported. The number of available groups is hardware dependent.

More details on the eXpressWare software can be found at:

<https://www.dolphinics.com/software.html>

Dolphin technical support and documentation

We do take software development and product testing seriously, please let us know your experience or any issue by sending an email to pci-support@dolphinics.com.

Additional information, installation manuals etc can be found at <http://www.dolphinics.com/px>

SISCI API resources can be found at

www.dolphinics.com/products/embedded-sisci-developers-kit.html

This release note contains a summary of the important changes made to eXpressWare. Please contact Dolphin for a complete list of changes.

Supported Hardware and configurations

Supported Dolphin products

This software release supports the following PCIe adapter cards.

The NTB software supports the following Dolphin adapter cards

- PXH810, PXH820, PXH830, PXH840, PXH841, PXH843, PXH844, PXH860

The Transparent Board Management software supports the following adapter cards

- PXH812, PXH822, PXH832, PXH842, PXH845, PXH846, PXH847, PXH848

Please chose another software download if you are using a not listed adapter card.

Supported Dolphin PCI Express switches

- IXS600 (PXH810 only)
- MXS824 (PXH830 and PXH820)
- MXS824 (PXH810 using a x8 iPass to dual x4 SFF-8644 cable)
- MXS924

Configurations supported by this release

The software release support the following configurations.

General use with PXH810:

- 2 to 14 nodes using multiple IXS600-HN switches.
- 2 to 12 nodes using MXS824 (using a x8 iPass to dual x4 SFF-8644 cable)
- 2 nodes using a single PCIe x8 cable.

General use with PXH820 and PXH830:

- 2 nodes using 1, 2, 4 (x4, x8, x16) MiniSAS-HD or PCIe 3.0 cables.
- 3 nodes using 1, 2 (x4 or x8) MiniSAS-HD or PCIe 3.0 cables.
- Up to 6 nodes x16 using one MXS824 switch.
- Up to 12 nodes x8 using one MXS824 switch.
- Up to 24 nodes x4 using one MXS824 switch.
- Up to 30 nodes x16 using multiple MXS824 switches.
- Up to 60 nodes x8 using multiple MXS824 switches.

NOTE: Please contact Dolphin for more information on large PCIe networks, some limitations may apply.

General use with PXH840:

- 2 nodes using 1 or 2 (x8) MPO 24 strand fiber cables.
- 3 nodes using 2 (x8) MPO 24 strand fiber cables.

Reflective memory use with with PXH810:

- 2 to 14 nodes using one IXS600-HN switch.
- 2 nodes using a single PCIe x8 iPass cable.

Reflective memory use with with PXH820 and PXH830:

- 2 nodes using 1, 2, 4 (x4, x8, x16) MiniSAS-HD or PCIe 3.0 cables.

- Up to 6 nodes x16 using one MXS824 switch.
- Up to 12 nodes x8 using one MXS824 switch.
- Up to 24 nodes x4 using one MXS824 switch.
- Up to 30 nodes x16 using multiple MXS824 switches.
- Up to 60 nodes x8 using multiple MXS824 switches.

Support for redundant fabrics

- Up to 5 Cards pr host connected directly or through separate switches are supported at the SISI level. SuperSockets supports fail-over from single adapter card to Ethernet.

PCI Express Hot Add with PXH820, PXH830 and PXH840 (Linux Only)

- PXH820 or PXH830 connected to PXH822, PXH832, MXH832, MXH833 installed in an expansion chassis.
- PXH820 or PXH830 connected to MXS824 in transparent mode, fan out to max 5 MXH832, PXH822 or PXH832 installed in an expansion chassis.
- PXH840 connected to a PXH842.

NOTE: Please contact Dolphin if you are planning to connect directly to non Dolphin target card or device.

Standard firmware revisions

Adapter / DIS release	PXH82x		PXH83x		PXH84x	
	MCU	EEPROM	MCU	EEPROM	MCU	EEPROM
5.19.2	8.12	2	8.12	11	8.11	
5.18.1	8.12	2	8.12	11	8.11	
5.17	8.12	2	8.12	11	8.11	
5.16	8.11	2	8.11	11	8.11	
5.15.2	8.11	2	8.11	11	8.11	
5.15.1	8.11	2	8.10	11	8.10	
5.14.0	8.10	2	8.10	11	8.6	
5.13.1	8.9	NA	8.4	11	8.6	

Support for OEM hardware

This version of Dolphin eXpressWare has general support for most Broadcom Gen3 NTB enabled chipset in various configurations and topologies. Please contact Dolphin for details and licensing information if you would like to run eXpressWare on your own hardware.

If you already are running eXpressWare on non Dolphin hardware, please contact your hardware vendor for additional information on how to upgrade your software.

Please note that Dolphin eXpressWare also support IDT and Microsemi PCIe chipset. Please contact Dolphin for more information.

General eXpressWare defaults and settings for PX

eXpressWare is tuned for general use and operations. In some cases, you need to tune some parameters to optimize resources for our use case.

- SISI Multicast
 - Default setting 4 groups, 2 Megabyte per segment.
 - Max setting 64 groups, 128 Gigabytes per segment.

Please consult the “Dolphin eXpressWare Installation and Reference Guide, section “Managing PCIe and eXpressWare Resources” for information how to tune eXpressWare parameters.

Dolphin eXpressWare PX release 5.19.2 Linux

Description of content: Clustering package for Linux.

Release category: GA

Target audience: Production systems.

Release date: 7th January 2022.

Current status: Available for download from <https://www.dolphinics.com/px>

New in DIS PX 5.19.2:

- Fixed unbinding of plx_dma driver from DMA functions of Dolphin adapters
- Added support for PXH832-H1 were Suppress Surprise down bit is enabled
- Added upgrade support for PXH860
- Added support for adapters with IPASS connectors connected to adapters with Mini SAS HD connectors. I.e., PXH810 can be connected to PXH830 or MXS824/MXS924 with special cable.
- Added support for Linux kernels up to 5.14
- Fixed handling of completion timeout on Root Port for transparent adapters.
- Fixed regression with Asymmetric topology introduced in 5.19.0
- Fixed driver crash in DSWITCH mode
- Fixed possible crash when aborting sysdma transfers on some systems
- Use more conservative PCIe MPS (max packet size) handling. By default (ntb_set_mps=1) to prevent automatic increase.
- General bug fixes and improvements.
- Installer support EL7 for Fedora 22, 23 and 24
- Added link speed (--link-speed) option to the Linux installer
- Fixed crash when IOMMU was disabled on some systems
- Improved deallocation of segments for smart-IO
- Added support for Supersockets on Ubuntu 20.04 with hwe-kernel
- Improved interrupt handling for global DMA
- Resetting the link with causes LUTs to be marked as zombies
- Fixed DMA driver hang on some systems
- Applied copy function patch for the unaligned crash issue on some ARM platforms.
- Added support for Ubuntu 20.04.2 LTS

Changes in previous releases:

DIS PX 5.18.1:

- Improved detection and reporting of old firmware.
- General bug fixes and improvements.
- Added 2x8 support for MXH830 adapters
- Fixed DMA performance optimization on ARM64 platforms.
- Added initial support for monitoring transparent downstream links in D-Switch mode.
- Fixed DMA hang on some systems
- General DMA improvements
- Fixed regression in session handling with MXS824 switch
- Fixed hardware descriptor index bug when using MSI interrupts for Global DMA
- Fixed problem with Global DMA engine hanging due to wrong SSID register content on some systems.

DIS PX 5.17.0:

- SISI
 - Added support for send-only multicast configurations.
 - Fixed bug in segment cleanup for shared segments that could cause segment to be unavailable for all users.
 - Increased max multicast segment size to 128 GB. Fixed 32 bit size limitations with internal copy function. Tested up to 4GB.
 - Fixed bug related to local DMA (memory to memory) with systems with IOMMU ON.
- Fixed issue upgrading PXH card firmware on some platforms.
- Fixed Ubuntu 18.04 installation issue.
- Do not report Unsupported Requests (UR) to the IRM.
- Add BDF information in dis_diag and dis_tool.
- General bug fixes and improvements.

DIS PX 5.16.0:

- Added support for system DMA with IOMMU ON (Off already supported)
- Added full support for all flavors of PXH84x with reduced number of FireFly (PXH843 – PXH848).
- Added support for Linux kernel $\geq 5.5.3$. Tested on Linux kernel 5.5.8
- SISI API
 - Added support for using multiple DMA channels.
 - Added support for registering more than one PCIe requester ID per SISI descriptor.
 - Fixed a crash when an invalid fdid was given to SCIBorrowDevice()
 - Allow SCIBorrowDevice() of PCI-PCI bridges in NT-Transp
- SmartIO
 - Fixed issue when some devices are behind an IOMMU, but other not.
 - Fixed issues with rescan when link goes up / down with multiple adapters.
 - More robust scanning.
 - Fixed crash during device lending when amd_iommu was enabled.
 - Fixed issue with RedHat 8 / new kernels Assertion (vdev->orig_dma_ops != NULL).
 - Fixed issue in NT-Transp detecting directly connected endpoints.

DIS PX 5.15.2:

- Improved detection and reporting of old firmware
- SmartIO – fixed potential assert in device scanning process

DIS PX 5.15.1:

- Fixed bug in SISI supporting larger than 4GB segments.
- Fixed multi endian issue with reflective memory test program
- PX Firmware 5.11 – fixes issue setting prefetch space size introduced in Firmware 5.10
- SmartIO 2.5.1
 - Improved scanning and error resilience, fixed dual adapter problem.

DIS PX 5.15.0:

- Increase max number of adapters from 4 to 5.

- SmartIO 2.5
 - SmartIO SISI functions stabilized.
 - Add support for `smartio_tool remove`.
 - Show ethernet device in `smartio_tool show`.
 - Support for multi-link in NT-Transp.
 - Fixed bug disabling nvidia persistence mode.
 - Fixed issue affecting SR-IOV VFs
- Fixed problem with MXS824 switch not being detected by the driver running on big endian host machines.
- SIA Installer: Fixed problem with the --install-all option
- User-space SuperSockets: Fixed problem with maximum number of connections decreasing over time.

DIS PX 5.14.0:

- Support for PXH820/822 Revision B (XMC)
- Increased maximum multicast segment size to 512 MB
- Supports up to kernel 5.3
- Added support for Debian 10
- Added support for Ubuntu 18.04 with HWE kernel
- SmartIO 2.4
 - Added support for reflective memory
 - Fixed scan speed regression in NT-Transparent mode
 - Fixed problem with Nvidia Persistence mode
 - Device Lending improvements.
- Initial support for X-Gene 3 processor
- Fixed problem with dis_diag reporting erroneous board temperature for PXH8xx
- Fixed problem with Device Lending not working on AMD Ryzen due to DPC interference.
- SISI:
 - Fixed problem compiling example programs
 - Fixed errors when using SCIRegisterSegmentMemory()
- SuperSockets:
 - Fixed problem with crash during accept() if NO_NATIVE_CONN is use inconsistently across the cluster.
- General bug fixes and improvements.

DIS PX 5.13.1:

- Support for larger MXS824 based networks.
- Support for PXH820 XMC
- Reduced system load for both internal and external DMA
- Improved SIA installers for all platforms. Added advanced configuration option allowing only required modules to be installed.
- Supports up to kernel 4.19
- SmartIO 2.1
 - Fixed issue with device lending NVIDIA GPUs with newer GPU drivers. Confirmed working with 418.39
 - MSI-X not working on kernel >= 4.4. Workaround implemented. Fix planned for eXpressWare 5.12
 - SISI SmartIO API Extension revisited and stabilized.
 - Device Lending improvements.
- SISI

- SISI virtual devices can now hold up to 32 instances of each resource type.
- Added function to retrieve information about SmartIO devices.
- Added support for Nvidia Xavier.
- Fixed problem compiling eXpressWare from tarball source.
- General bug fixes and improvements.

Included software:

- SuperSockets (kernel)
 - Ultra fast, low latency Berkeley Sockets API (TCP, UDP, UDP multicast) for PCIe.
 - Local and remote socket communication acceleration (accelerated loop-back device support local IP and localhost address).
- SuperSockets user space
 - User space version of SuperSockets. Provides lower latency than the kernel version, but proves a limited number of socket functionality. Currently only TCP.
 - Support communication to systems running Windows SuperSockets.
- SISI API 2.0.2
 - Shared memory (DMA, PIO, RDMA, Interrupts).
 - Reflective memory/multicast.
 - SmartIO Extension 1.0
 - PCIe peer to peer communication (FPGAs, GPUs, NVMe etc).
 - Full connectivity to other systems running Windows, RTX or VxWorks.
- SmartIO 2.4
 - Device Lending
 - SISI API SmartIO Extension.
- TCP/IP driver
 - Full IP networking over PCIe to other nodes running Linux.
- Network Installer (SIA)
 - Installs the above software on a cluster of computers interconnected with Ethernet.
- Transparent Board Management
 - Transparent board management software for transparent cards PXH812, PXH832 and PXH842.

Supported architectures:

The software supports the following architectures and platforms:

- Intel x86 / x64
- ARM32, Jetson Tegra TK1
- ARM64, Jetson Tegra TX1, TX2. Xavier
- ARM64v8 Applied Micro X-Gene

Tested and supported OS platforms:

Dolphin strive to support all major Linux distributions and kernels from 2.6.32 and up. This release has been tested on these platforms but are expected to work on many more. Please let us know if you run into problems or need another kernel:

Linux Kernel 2.6.32 - 5.5.8

- CentOS 8 x86_64
- CentOS 7 x86_64
- CentOS 6 x86_64
- CentOS 5 x86
- Ubuntu 14.04 LTS aarch64 / Mustang ARM64

- OpenSUSE Leap 15.1
- Ubuntu 14.04 x86_64
- Ubuntu 16.04 x86_64
- Ubuntu 18.04 x86_64
- Debian 7 x86_64
- Debian 8 x86_64
- Debian 9 x86_64
- Debian 10 x86_64
- Fedora 25 x86_64

RedHawk Linux from Concurrent Real-Time is supported. Please contact Concurrent for access to drivers.

We also provide OpenRC init scripts as used by Gentoo and other distributions, please contact Dolphin Support for more detailed information.

Cluster installation requirements:

- All nodes connected and properly configured with Ethernet.
 - Non Ethernet configurations optional, contact Dolphin.

Installation and management:

- RPM based via Self Installing Archive (SIA).
- Automatic configuration via Interconnect manager.
- Centralized monitoring and diagnostic.
 - Both Linux and Windows supported as GUI platform.

High availability features:

- Nodes can join and leave cluster (node reboot, power cycled) any time without disturbing communication between other nodes.
- Power cycling the switch will cause SuperSockets to fail over to Ethernet while cluster is automatically reconfiguring.
- Unplugging a cable will cause SuperSockets to fail over to Ethernet for all connections affected. SuperSockets will automatically re-establish communication when cable is inserted.

Bundled (major) management tools:

- dis_diag (diagnostic tool)
- dis_admin (cluster monitor and manager GUI)
- networkmanager (cluster configuration and maintenance demon)
- dis_netconfig (configuration editor GUI)

Bundled (major) demo tools:

- Scibench2 (SISCI based PIO throughput benchmark)
- scipp (SISCI based ping pong benchmark)
- dma_bench (SISCI based DMA benchmark)
- interrupt_bench (SISCI based remote system interrupt benchmark)
- reflective_bench (SISCI based reflective memory benchmark)
- latency_bench (TCP latency benchmark, runs on any IP network including SuperSockets)

Firmware upgrade:

The Driver installer will detect and suggest to automatically update the firmware during installation if an update is required (new firmware may be included in software distribution). Please upgrade by running `/opt/DIS/sbin/upgrade_eeprom.sh`. A reboot is required after firmware upgrade.

Dolphin eXpressWare PX release 5.19.2 Windows

Description of content: Clustering package for Windows.

Release category: GA

Release date: 7th January 2022

Current status: Available for download from

<https://www.dolphinics.com/px>

New in DIS PX 5.19.2:

- Improved detection of DMA hardware PEX ids to prevent conflicts with other PEX switches.
- Improved memory handling allocating large segments
- General improvements
- Improved Windows installer

Changes in previous releases:

DIS PX 5.18.1:

- Fixed crash on transparent adapter installation.
- Fixed completion timeout on Root Port for transparent adapters.
- Fixed problem with Global DMA engine hanging due to wrong SSID register content on some systems.
- Fixed hardware descriptor index bug when using MSI interrupts for Global DMA.
- Improved detection and reporting of old firmware.
- Improved driver handling of transparent adapters

DIS PX 5.16.0:

- SISI API
 - Added support for using multiple DMA channels.
 - Added support for registering more than one PCIe requester ID per SISI descriptor.
- Prevent Board Management Software installation on Compute nodes.

DIS PX 5.15.2:

- Added support for SISI Hot Add support for transparent devices.
- Improved detection and reporting of old firmware.

DIS PX 5.15.1:

- Fixed bug in SISI supporting larger than 4GB segments.
- Fixed multi endian issue with reflective memory test program.

DIS PX 5.15.0:

- Increase max number of adapters from 4 to 5.
- User-space SuperSockets: added a listen thread to accept incoming connections.

DIS PX 5.14.0:

- Support for PXH820/822 Revision B (XMC)
- Increased maximum multicast segment size to 512 MB
- Fixed problem with dis_diag reporting erroneous board temperature for PXH8xx

- Improved allocation of large memory areas
- Fixed IRM failure to load on certain runtime contexts
- Fixed detection of RootPort's BDF on some systems
- Fixed deadlock or crash due to improper computation of CompletionTimeout offset inside PCIe AER capability
- General bug fixes and improvements.

DIS PX 5.13.1:

- Support for larger MXS824 based networks.
- General bug fixes and improvements.

Included software:

- SuperSockets
 - Ultra fast, low latency WinSock2 Sockets API (TCP) for PCIe
 - Local and remote socket communication acceleration (accelerated loop-back device support local IP and localhost address).
 - Connectivity to other systems running Linux user space SuperSockets.
- SISI API V2.0
 - Shared memory (DMA, PIO, RDMA, Interrupts)
 - Reflective memory/multicast.
 - PCIe peer to peer communication (FPGAs, GPUs etc)
 - Full connectivity to other systems running Linux, RTX or VxWorks.
- TCP/IP driver (IPoPCIe, Only included in installers for Windows Vista and newer)
 - Private network to other nodes running Windows.
 - Routing to other network (Connect your PCIe cluster to a 10G Ethernet up-link)
- Transparent Board Management
 - Transparent board management software for transparent cards PXH812, PXH832 and PXH842.

Supported OS platforms:

Windows Vista - 32 bit

Windows Vista - 64 bit

Windows Server 2008 - 32 bit

Windows Server 2008 - 64 bit

Windows Server 2008 R2 - 64 bit

Windows Server 2012 R2 – 64 bit

Windows Server 2016 – 64 bit

Windows Server 2019 – 64 bit

Windows 7 - 32 bit

Windows 7 - 64 bit

Windows 8 - 32 bit

Windows 8 - 64 bit

Windows 8.1 – 64 bit

Windows 10 – 64 bit

Cluster installation requirements:

- All nodes connected and properly configured with Ethernet.
 - Non Ethernet configurations optional, contact Dolphin.

Installation and management:

- Windows MSI Installer package.
- Automatic configuration via Interconnect manager.
- Centralized monitoring and diagnostic.
 - Both Linux and Windows supported as GUI platform.

High availability features:

- Nodes can join and leave cluster (node reboot, power cycled) any time without disturbing communication between other nodes.
- SuperSockets will fail-over to Ethernet if Dolphin Express network is unavailable during application startup.

Bundled (major) management tools:

- dis_diag (diagnostic tool)
- dis_admin (cluster monitor and manager GUI)
- networkmanager (cluster configuration and maintenance demon)
- dis_netconfig (configuration editor GUI)

Bundled (major) demo tools:

- Scibench2 (SISCI based PIO throughput benchmark)
- scipp (SISCI based ping pong benchmark)
- dma_bench (SISCI based DMA benchmark)
- interrupt_bench (SISCI based remote system interrupt benchmark)
- reflective_bench (SISCI based reflective memory benchmark)
- latency_bench (TCP latency benchmark, runs on any IP network including SuperSockets)

Firmware upgrade:

PXH cards may need a firmware update to support the 5.x.x series of software. After installing the drivers, please run the command:

Start PowerShell with administrative capabilities (Press Windows+X, select Windows PowerShell (Admin))

```
PS > cd "${env:ProgramFiles}\Dolphin Express PX\Util"
PS > Set-ExecutionPolicy AllSigned -Scope Process
PS > .\upgrade_eeprom.ps1 --upgrade
```

Please carefully review the output from the upgrade utility.

A reboot is required after upgrading the firmware. Please contact pci-support@dolphinics.com if you have any problems.

Dolphin eXpressWare PX release 5.19.2 RTX

Description of content: Clustering package for RTX

Release category: GA

Release date: 7th January 2022.

Current status: Available. Contact Dolphin.

New in DIS MX 5.19.2:

- General bug fixes and improvements.

Changes in previous releases:

DIS MX 5.18.1:

- General bug fixes and improvements.

DIS MX 5.17.0:

- SISI
 - Added support for send-only multicast configurations.
 - Fixed bug in segment cleanup for shared segments that could cause segment to be unavailable for all users.
 - Increased max multicast segment size to 128 GB. Fixed 32 bit size limitations with internal copy function.
- General bug fixes and improvements.

DIS PX 5.15.2:

- Improved detection and reporting of old firmware.

DIS PX 5.15.0:

- Increase max number of adapters from 4 to 5.

DIS PX 5.14.0:

- Support for PXH820/822 Revision B (XMC)
- Increased maximum multicast segment size to 512 MB
- Fixed problem with dis_diag reporting erroneous board temperature for PXH8xx
- General bug fixes and improvements.

DIS PX 5.13.1:

- Support for larger MXS824 based networks.
- General bug fixes and improvements.

Included software:

- SISI API V2.0.2
 - Shared memory (DMA, PIO, RDMA, Interrupts)
 - Reflective memory/multicast
 - PCIe peer to peer communication (FPGAs, GPUs etc)
 - Full connectivity to other systems running Linux, Windows or VxWorks.

Supported OS platforms:

Windows Server 2008 R2 - 64 bit

Windows Server 2012 R2 – 64 bit

Windows Server 2016 – 64 bit
Windows 7 - 64 bit
Windows 8.1 – 64 bit
Windows 10 – 64 bit

Installation and management:

- Windows MSI Installer package.

High availability features:

- Nodes can join and leave cluster (node reboot, power cycled) any time without disturbing communication between other nodes.

Bundled (major) management tools:

- dis_diag (diagnostic tool)

Bundled (major) demo tools:

- Scibench2 (SISCI based PIO throughput benchmark)
- scipp (SISCI based ping pong benchmark)
- dma_bench (SISCI based DMA benchmark)
- interrupt_bench (SISCI based remote system interrupt benchmark)
- reflective_bench (SISCI based reflective memory benchmark)

Firmware upgrade:

PXH cards may need a firmware update to support the 5.x.x series of software. After installing the drivers, please run the command:

```
C:\Program Files\Dolphin Express RTSS\Util\upgrade_eeeprom.cmd --upgrade
```

to upgrade the firmware. A reboot is required after upgrading the firmware. Please contact pci-support@dolphinics.com if you have any problems.

Dolphin eXpressWare PX release 5.19.2 VxWorks

Description of content: Clustering package for VxWorks

Release category: GA

Release date: 7th January 2022.

Current status: Available. Contact Dolphin.

New in DIS PX 5.19.2:

- Added support for MCH663 D-Switch on Linux and VxWorks 7
- Fixed regression with Asymmetric topology on PCH482
- Added support for MCH663 D-Switch
- General bug fixes and improvements.
- Extended adapter installer support
- Fixed issue with cache allocator running out of memory
- Added support for multiple MSI-X vectors for VxWorks 7

Changes in previous releases

DIS PX 5.18.1:

- Fixed timer tasks crash during init on some configurations
- Improved driver handling of transparent adapters

DIS PX 5.17.0:

- Added support for VxWorks 7 SR0640
- SISI
 - Added support for send-only multicast configurations.
 - Fixed bug in segment cleanup for shared segments that could cause segment to be unavailable for all users.
 - Increased max multicast segment size to 128 GB. Fixed 32 bit size limitations with internal copy function.
- General bug fixes and improvements.

DIS PX 5.16.0:

- Added support for VxWorks 7 SR0620 with LLVM/Clang compiler
- Fixed VxWorks initialization ordering
- Added CDF parameter EXPRESSWARE_SLOT_0_NODEID to explicitly define the auto-configuration NodeId if the geographical address (slot number) is reported as 0 by the BSP.
- SISI API
 - Added support for using multiple DMA channels.
 - Added support for registering more than one PCIe requester ID per SISI descriptor.

DIS PX 5.15.2:

- Improved detection and reporting of old firmware.

DIS PX 5.15.1:

- Fixed bug in SISI supporting larger than 4GB segments.
- Fixed multi endian issue with reflective memory test program.

DIS PX 5.15.0:

- Increase max number of adapters from 4 to 5.
- Verbosity control for driver output.
- Fixed problem with MXS824 switch not being detected by the driver running on big endian host machines.

DIS PX 5.14.0:

- Support for PXH820/822 Revision B (XMC)
- Increased maximum multicast segment size to 512 MB
- Fixed problem with dis_diag reporting erroneous board temperature for PXH8xx
- Support for VxWorks 6.8 on PPC
- General bug fixes and improvements.

DIS PX 5.13.1:

- Support for larger MXS824 based networks.
- General bug fixes and improvements.

Included software:

- SISCI API V2.0.2
 - Shared memory (DMA, PIO, RDMA, Interrupts)
 - Reflective memory/multicast
 - PCIe peer to peer communication (FPGAs, GPUs etc)
 - Full connectivity to other systems running Linux, RTX or VxWorks.

Supported OS platforms:

VxWorks 6.8 PPC32 SMP

VxWorks 6.9 Intel x64 SMP

VxWorks 6.9 Intel x86 SMP

VxWorks 7.0 Intel x64 SMP

VxWorks 7.0 Intel x86 SMP

Note: AMP and User-space communication not supported.

Installation and management:

- Windows MSI Installer package.
- Linux ZIP file.

High availability features:

- Nodes can join and leave cluster (node reboot, power cycled) any time without disturbing communication between other nodes.

Bundled (major) management tools:

- dis_diag (diagnostic tool)

Bundled (major) demo tools:

- Scibench2 (SISCI based PIO throughput benchmark)
- scipp (SISCI based ping pong benchmark)
- dma_bench (SISCI based DMA benchmark)
- interrupt_bench (SISCI based remote system interrupt benchmark)
- reflective_bench (SISCI based reflective memory benchmark)

Firmware upgrade:

PXH cards may need a firmware update to support the 5.x.x series of software. After installing the drivers, please run the command:

```
upgrade_eeprom.cmd --upgrade
```

to upgrade the firmware. A reboot is required after upgrading the firmware. Please contact pci-support@dolphinics.com if you have any problems.